

HIT-HY 170

en	This safety data sheet file is issued for the following production lots: 1. Version 2.X is valid for HIT-HY 170 with a maximum expiration date of 12/2022 (see foil pack manifold) 2. Version 3.0 is valid for HIT-HY 170 with a minimum expiration date of 01/2023 (see the foil pack manifold)
de	Diese Sicherheitsdatenblatt-Datei betrifft die folgenden Fertigungslose: 1. Version 2.X ist gültig für HIT-HY 170 mit einem Haltbarkeitsdatum bis 12/2022 (siehe Verbindungsteil) 2. Version 3.0 ist gültig für HIT-HY 170 mit einem Haltbarkeitsdatum ab 01/2023 (siehe Verbindungsteil)
nl	Dit veiligheidsinformatiebladbestand wordt afgegeven voor de volgende productie-lots: 1. Versie 2.X is geldig voor HIT-HY 170 met een maximale houdbaarheidsdatum tot 12/2022 (zie foliepak verdeler) 2. Versie 3.0 is geldig voor HIT-HY 170 met een minimale houdbaarheidsdatum tot 01/2023 (zie foliepak verdeler)
fr	Ce fichier de données de sécurité est délivré pour les lots de production suivants : 1. La version 2.X est valide pour HIT-HY 170 avec une date d'expiration maximale de 12/2022 (voir le raccord de cartouche souple) 2. La version 3.0 est valide pour HIT-HY 170 avec une date d'expiration maximale de 01/2023 (voir le raccord de cartouche souple)
da	Denne sikkerhedsdatabladsfil er udgivet for følgende produktions lots: 1. Version 2.X er gældende for HIT-HY 170 med en maksimal udløbsdato d. 12/2022 (se foliepakkens manifold) 2. Version 3.0 er gældende for HIT-HY 170 med en mindste udløbsdato d. 01/2023 (se foliepakkens manifold)
sv	Denna säkerhetsdatabladsfil har utfärdats för följande tillverkningspartier: 1. Version 2.X är giltig för HIT-HY 170 med ett sista giltighetsdatum den 12/2022 (se folieförpackningens grenrör) 2. Version 3.0 är giltig för HIT-HY 170 med ett första giltighetsdatum den 01/2023 (se folieförpackningens grenrör)
fi	Tämä käyttöturvallisuustiedote koskee seuraavia tuotantoeriä: 1. Versio 2.X koskee HIT-HY 170 -tuotetta, jonka viimeinen käyttöpäivämäärä on 12/2022 tai sitä ennen (ks. foliopakkauksen taite) 2. Versio 3.0 koskee HIT-HY 170 -tuotetta, jonka viimeinen käyttöpäivämäärä on 01/2023 tai sen jälkeen (ks. foliopakkauksen taite)
hu	Ezt a biztonsági adatlapot a következő gyártási tételekhez bocsátják ki: 1. Az 2.X változat legfeljebb 2022/12 lejáratú dátummal érvényes a HIT-HY 170-re (lásd a fóliacsomag sokszorosított iratát) 2. Az 3.0 változat legalább 2023/01 lejáratú dátummal érvényes a HIT-HY 170-re (lásd a fóliacsomag sokszorosított iratát)
es	Este archivo de hoja de datos de seguridad se emite para los siguientes lotes de producción: 1. Versión 2.X es válida para HIT-HY 170 con una fecha de caducidad máxima de 12/2022 (consulte el colector de láminas) 2. Versión 3.0 válida para HIT-HY 170 con una fecha de caducidad mínima de 01/2023 (consulte el colector de láminas)
pt	Este ficheiro com ficha de dados de segurança é emitido para os seguintes lotes de produção: 1. A versão 2.X é válida para a HIT-HY 170 com um prazo máximo de validade até 12/2022 (ver as diversas embalagens) 2. A versão 3.0 é válida para a HIT-HY 170 com um prazo mínimo de validade até 01/2023 (ver as diversas embalagens)
it	Questo file della scheda tecnica di sicurezza è rilasciato per i seguenti lotti di produzione: 1. La versione 2.X è valida per HIT-HY 170 con data di scadenza massima 12/2022 (vedere la giunzione della confezione) 2. La versione 3.0 è valida per HIT-HY 170 con data di scadenza minima 01/2023 (vedere la giunzione della confezione)
pl	Ten plik arkusza danych bezpieczeństwa jest wydany dla następujących części produkcyjnych: 1. Wersja 2.X obowiązuje w przypadku HIT-HY 170 z maksymalnym dniem rozpoczęcia pracy 12/2022 (patrz opakowanie foliowe) 2. Wersja 3.0 obowiązuje w przypadku HIT-HY 170 z minimalnym dniem rozpoczęcia pracy 01/2023 (patrz opakowanie foliowe)
ru	Этот файл сертификата безопасности предоставлен для следующих партий продукции: 1. Версия 2.X действительна для HIT-HY 170 с максимальным сроком годности до 12.2022 г. (см. присоединительную часть на капсуле) 2. Версия 3.0 действительна HIT-HY 170 с минимальным сроком годности до 01.2023 г. (см. присоединительную часть на капсуле)
el	Το παρόν δελτίο δεδομένων ασφαλείας εκδίδεται για τις ακόλουθες παρτίδες παραγωγής: 1. Η έκδοση 2.X ισχύει για το HIT-HY 170 με μέγιστη ημερομηνία λήξης τον 12/2022 (βλέπε διανομέα συσκευασίας μεμβράνης) 2. Η έκδοση 3.0 ισχύει για το HIT-HY 170 με ελάχιστη ημερομηνία λήξης τον 01/2023 (βλέπε τον διανομέα της συσκευασίας μεμβράνης)
cs	Tento soubor s bezpečnostním listem je vystaven pro tyto výrobní závody 1. Verze 2.X je platná pro HIT-HY 170 s maximálním datem expirace 12/2022 (viz fólie balení) 2. Verze 3.0 je platná pro HIT-HY 170 s minimálním datem expirace 01/2023 (viz fólie balení)
bg	Този информационен лист за безопасност се публикува за следните производствени партии: 1. Версия 2.X е валидна за HIT-HY 170 с максимален срок на валидност до 12.2022 г. (вж. фолийна опаковка за колектор) 2. Версия 3.0 е валидна за HIT-HY 170 с минимален срок на изтичане 01.2023 г. (вж. фолийна опаковка за колектор)
lv	Šo drošības datu lapa ir izsniegta šādām ražojumu partijām: 1. Versija 2.X ir derīga izstrādājumam HIT-HY 170, kura maksimālais derīguma termiņš ir 2022. gada maijs (skatīt folija iepakojuma kolektoru) 2. Versija 3.0 ir derīga izstrādājumam HIT-HY 170, kura minimālais derīguma termiņš ir 2023. gada jūnijs (skatīt folija iepakojuma kolektoru)
lt	Šis saugos duomenų lapo failas išduodamas šioms gamybos partijoms: 1. 2.X versija galioja HIT-HY 170, kurios maksimali galiojimo data – 2022-12 (žr. folinių pakuočių rinkinį) 2. 3.0 versija galioja HIT-HY 170, kurios minimali galiojimo data – 2023-01 (žr. folinių pakuočių rinkinį)
sk	Tento súbor bezpečnostných údajov sa vydáva pre tieto výrobné šarže: 1. Verzia 2.X je platná pre HIT-HY 170 s maximálnym dátumom expirácie 12/2022 (pozrite si údaj na fólii balenia) 2. Verzia 3.0 je platná pre HIT-HY 170 s minimálnym dátumom expirácie 01/2023 (pozrite si údaj na fólii balenia)
sl	Datoteka z varnostnim listom je izdana za naslednje proizvodne serije: 1. Različica 2.X je veljavna za izdelek HIT-HY 170 z maksimalnim datumom poteka veljavnosti: 12/2022 (glejte pakiranje) 2. Različica 3.0 je veljavna za izdelek HIT-HY 170 z minimalnim datumom poteka veljavnosti: 01/2023 (glejte pakiranje)

HIT-HY 170

et	See ohutuskaardi fail on välja antud järgmistele tootepartidele: 1. Versioon 2.X kehtib tootele HIT-HY 170 viimase säilimiskuupäevaga 12/2022 (vt fooliumpakendi hargnemiskohta) 2. Versioon 3.0 kehtib tootele HIT-HY 170 esimese säilimiskuupäevaga 01/2023 (vt fooliumpakendi hargnemiskohta)
ro	Acest fișier cu date tehnice de securitate este emis pentru următoarele locuri de producție: 1. Versiunea 2.X este valabilă pentru HIT-HY 170 cu data maximă de expirare 12/2022 (a se vedea racordul pentru cartușe din folie) 2. Versiunea 3.0 este valabilă pentru HIT-HY 170 cu data minimă de expirare 01/2023 (a se vedea racordul pentru cartușe din folie)
hr	Ovaj sigurnosno-tehnički list izdaje se za sljedeće proizvodne serije: 1. Verzija 2.X vrijedi za HIT-HY 170 s maksimalnim rokom trajanja do 12/2022 (vidjeti razvodnik iz folije) 2. Verzija 3.0 vrijedi za HIT-HY 170 s minimalnim rokom trajanja do 01/2023 (vidjeti razvodnik iz folije)
tr	Bu güvenlik bilgi formu dosyası aşağıdaki üretim partileri için hazırlanmıştır: 1. Versiyon 2.X, maksimum son kullanma tarihi 12/2022 olan HIT-HY 170 için geçerlidir (bkz. folyo paketi manifoldu) 2. Versiyon 3.0, inimumm son kullanma tarihi 01/2023 olan HIT-HY 170 için geçerlidir (bkz. folyo paketi manifoldu)
uk	Цей файл сертифіката безпеки надано для наступних партій продукції: 1. Версія 2.X дійсна для HIT-HY 170 з максимальним терміном придатності до 12.2022 р. (див. приєднувальну частину на капсулі) 2. Версія 3.0 дійсна для HIT-HY 170 з мінімальним терміном придатності до 01.2023 р. (див. приєднувальну частину на капсулі)
zh	本安全数据表文件针对以下生产批次发布： 1. 版本 2.X 对 HIT-HY 170 有效，最长失效日期为 2022 年 12 月（参见箔包装歧管） 2. 版本 3.0 对 HIT-HY 170 有效，最短失效日期为 2023 年 1 月（参见箔包装歧管）
ar	يتم إصدار ملف صحيفة بيانات السلامة لتشغيلات الإنتاج التالية: 1. الإصدار 2.X صالح لـ HIT-HY 170 بعد أقصى لتاريخ انتهاء الصلاحية هو 2022/12 (انظر العبوة المصنوعة من رقائق الألومنيوم) 2. الإصدار 3.0 صالح لـ HIT-HY 170 على الأقل لتاريخ انتهاء الصلاحية هو 2023/1 (انظر العبوة المصنوعة من رقائق الألومنيوم)
ja	この安全性データシートファイルは、次の生産ロット用に発行されています： 1. バージョン 2.X は、有効期限が最大 2022 年 12 月までの HIT-HY 170 に対して有効です（フォイルパック連結部に表示） 2. バージョン 3.0 は、有効期限が 2023 年 1 月以降の HIT-HY 170 に対して有効です（フォイルパック連結部に表示）
sr	Datoteka bezbednosnog lista se izdaje za sledeće proizvodne serije: 1. Verzija 2.X je dostupna za HIT-HY 170 sa maksimalnim datumom isteka 12/2022 (pogledajte ivicu pakovanja od folije) 2. Verzija 3.0 je dostupna za HIT-HY 170 sa minimalnim datumom isteka 01/2023 (pogledajte ivicu pakovanja od folije)
ms	Fail helaian data keselamatan ini dikeluarkan untuk lot pengeluaran yang berikut: 1. Versi 2.X adalah sah untuk HIT-HY 170 dengan tarikh tamat tempoh maksimum pada 12/2022 (lihat manifold pek kerajang) 2. Versi 3.0 adalah sah untuk HIT-HY 170 dengan tarikh tamat tempoh minimum pada 01/2023 (lihat manifold pek kerajang)
ko	본 안전보건자료는 다음 제품 로트에 대해 발급되었습니다. 1. 버전 2.X(은)는 HIT-HY 170에 대해 유효하며, 최대 만료 기한은 2022년 12월입니다(호일 팩 매니폴드 참조) 2. 버전 3.0(은)는 HIT-HY 170에 대해 유효하며, 최소 만료 기한은 2023년 1월입니다(호일 팩 매니폴드 참조)
id	File lembar data keselamatan ini diterbitkan untuk lot produksi berikut: 1. Versi 2.X berlaku untuk HIT-HY 170 dengan tanggal kedaluwarsa maksimum 12/2022 (lihat foil pack manifold) 2. Versi 3.0 berlaku untuk HIT-HY 170 dengan tanggal kedaluwarsa minimum 01/2023 (lihat foil pack manifold)
he	קובץ גיליון נתוני בטיחות זה מונפק עבור מגרשי הייצור הבאים: 1. גרסה 2.X תקפה ל-HIT-HY 170 עם תאריך תפוגה מקסימלי של 12/2022 (ראה יריעת foil pack) 2. גרסה 3.0 תקפה ל-HIT-HY 170 עם תאריך תפוגה מינימלי של 01/2023 (ראה יריעת foil pack)
th	แผ่นข้อมูลด้านความปลอดภัยนี้จัดทำขึ้นเพื่อสำหรับการผลิตดังต่อไปนี้: 1. เวอร์ชัน 2.X ใช้ได้กับ HIT-HY 170 ที่มีวันหมดอายุไม่เกิน 12/2022 (โปรดดูแผ่นพับห่อฟอยล์) 2. เวอร์ชัน 3.0 ใช้ได้กับ HIT-HY 170 ที่มีวันหมดอายุขั้นต่ำ 01/2023 (โปรดดูแผ่นพับห่อฟอยล์)
vi	Tệp bảng dữ liệu an toàn này được phát hành cho các lô sản xuất sau: 1. Phiên bản 2.X hợp lệ cho HIT-HY 170 với ngày hết hạn tối đa là 12/2022 (xem ống keo cấy thép) 2. Phiên bản 3.0 hợp lệ cho HIT-HY 170 với ngày hết hạn tối thiểu là 01/2023 (xem ống keo cấy thép)
zh tw	下列生產批次將獲核發本安全資料表檔案： 1. 2.X 版適用於 HIT-HY 170，最長到期日 12/2022（請見鋁箔包打字紙） 2. 3.0 版適用於 HIT-HY 170，最短到期日 01/2023（請見鋁箔包打字紙）
kk	Бұл қауіпсіздік паспорты мына өндірістік партиялар үшін шығарылады: 1. 2.X нұсқасы жарамдылық мерзімі көп уақытты (12/2022) қамтитын HIT-HY 170 үшін жарамды (жұқалтыр қаптаманы қараңыз) 2. 3.0 нұсқасы жарамдылық мерзімі аз уақытты (01/2023) қамтитын HIT-HY 170 үшін жарамды (жұқалтыр қаптаманы қараңыз)

HIT-HY 170

Safety information for 2-Component-products

Issue date: 22/09/2021

Revision date: 22/09/2021

Supersedes: 23/03/2020

Version: 3.0

SECTION 1: Kit identification

1.1 Product identifier

Product name

HIT-HY 170



Product code

BU Anchor

1.2 Details of the supplier of the Safety information for 2-Component-products

Hilti (New Zealand) Ltd.
Level 1, Building B 600 South Road
Ellerslie
1051 Auckland - New Zealand
T +64 9 571 9995
, 800 444 584 toll free - F +64 9526 7780
servicenz@hilti.com

SECTION 2: General information

Storage

Storage temperature : 5 - 25 °C

A SDS for each of these components is included. Please do not separate any component SDS from this cover page

This Kit should be handled in accordance with good laboratory practices and appropriate personal protective equipment should be used

SECTION 3:

Classification of the Product


2.1. Classification of the substance or mixture

EYDA-2
SESK-1
AEAH-1
AECH-1

6.4A: Eye Irrit. 2
6.5B: Skin Sens. 1
9.1A: Aquatic Acute 1
9.1A: Aquatic Chronic 1

2.2. Label elements

Hazard pictograms (GHS NZ)



Signal word (GHS NZ)

Warning

Hazard statements (GHS NZ)

H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H410 - Very toxic to aquatic life with long lasting effects.

Precautionary statements (GHS NZ)

P280 - Wear eye protection, protective clothing, protective gloves.
P262 - Do not get in eyes, on skin, or on clothing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P302+P352 - IF ON SKIN: Wash with plenty of water/...

HIT-HY 170

Safety information for 2-Component-products


P337+P313 - If eye irritation persists: Get medical advice/attention.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

2.3. Other hazards not contributing to the classification

No additional information available

Additional information

2-Component-foilpack, contains:
Component A: Urethane methacrylate resin, inorganic filler
Component B: Dibenzoyl peroxide, phlegmatized



Name	General description	Quantity	Unit	Classification according to the United Nations GHS
HIT-HY 170, B		1	pcs	Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
HIT-HY 170, A		1	pcs	Eye Irrit. 2, H319 Skin Sens. 1, H317

SECTION 4: General advice

General advice

For professional users only

SECTION 5: Safe handling advice

General measures	Spilled material may present a slipping hazard
Environmental precautions	Prevent entry to sewers and public waters Notify authorities if liquid enters sewers or public waters
Storage conditions	Keep cool. Protect from sunlight.
Precautions for safe handling	Wear personal protective equipment Avoid contact with skin and eyes Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work Provide good ventilation in process area to prevent formation of vapour
Methods for cleaning up	This material and its container must be disposed of in a safe way, and as per local legislation Mechanically recover the product Store away from other materials.
For containment	Collect spillage.
Incompatible materials	Sources of ignition Direct sunlight
Incompatible products	Strong bases Strong acids

SECTION 6: First aid measures

First-aid measures after eye contact	Rinse immediately with plenty of water Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists
First-aid measures after ingestion	Rinse mouth Get medical advice/attention. Do not induce vomiting Obtain emergency medical attention
First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air

HIT-HY 170

Safety information for 2-Component-products

First-aid measures after skin contact	Allow the victim to rest Wash contaminated clothing before reuse. Wash with plenty of water/...
First-aid measures general	If skin irritation or rash occurs: Get medical advice/attention. Take off immediately all contaminated clothing. Never give anything by mouth to an unconscious person If you feel unwell, seek medical advice (show the label where possible)
Symptoms/effects after eye contact	May cause severe irritation
Symptoms/effects after skin contact	May cause an allergic skin reaction.

SECTION 7: Fire fighting measures

Firefighting instructions	Use water spray or fog for cooling exposed containers Exercise caution when fighting any chemical fire Prevent fire fighting water from entering the environment
Protection during firefighting	Self-contained breathing apparatus Do not enter fire area without proper protective equipment, including respiratory protection
Hazardous decomposition products in case of fire	Thermal decomposition generates : Carbon dioxide Carbon monoxide

SECTION 8: Other information

No data available

HIT-HY 170, A

Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

Issue date: 22/09/2021

Revision date: 22/09/2021

Supersedes: 23/03/2020

Version: 3.0

SECTION 1: Identification of the hazardous chemical and of the supplier

1.1 Product identifier

Product name HIT-HY 170, A
Product form Mixture
Product code BU Anchor

1.2 Other means of identification

No additional information available

1.3 Relevant identified uses of the substance or mixture and uses advised against

Recommended use Composite mortar component for fasteners in the construction industry
Restrictions on use For professional use only

1.4 Supplier's details

Supplier

Hilti (New Zealand) Ltd.
Level 1, Building B 600 South Road
Ellerslie
1051 Auckland - New Zealand
T +64 9 571 9995
, 800 444 584 toll free - F +64 9526 7780
servicenz@hilti.com

Department issuing data specification sheet

Hilti Entwicklungsgesellschaft mbH
Hiltistraße 6
86916 Kaufering - Deutschland
T +49 8191 906876
anchor.hse@hilti.com

1.5. Emergency phone number

Emergency number Schweizerisches Toxikologisches Informationszentrum – 24h Service
+41 44 251 51 51 (international)
+64 9 571 9995
; 800 444 584 toll free

Country	Organisation/Company	Address	Emergency number
New Zealand	National Poisons Centre		0800 623 000

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

HSNO Approval Number HSR002544

6.4A Serious eye damage/eye irritation, Category 2
6.5B Skin sensitisation, Category 1

2.2. Label elements

GHS NZ labelling

Hazard pictograms (GHS NZ)



GHS07

Signal word (GHS NZ)

Contains

Hazard statements (GHS NZ)

Prevention

Warning

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (10 – 25 %) ; 2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (1 – 2.5 %)

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

P280 - Wear eye protection, protective clothing, protective gloves.

HIT-HY 170, A

Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

Response

P262 - Do not get in eyes, on skin, or on clothing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P302+P352 - IF ON SKIN: Wash with plenty of water/...

P337+P313 - If eye irritation persists: Get medical advice/attention.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

2.3. Other hazards not contributing to the classification

No additional information available

SECTION 3: Composition and information of the ingredients of the hazardous chemical

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	Conc.	Classification according to GHS NZ
2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol	(CAS-No.) 27813-02-1	10 – 25	Flam. Liq. Not classified Acute Tox. Not classified (Oral) 6.4A: Eye Irrit. 2A, H319 6.5B: Skin Sens. 1, H317 9.1D: Aquatic Acute 3, H402 9.1C: Aquatic Chronic 3, H412
2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester	(CAS-No.) 2082-81-7	1 – 2.5	Acute Tox. Not classified (Oral) 6.5B: Skin Sens. 1, H317
1,1'-(p-tolylimino)dipropan-2-ol	(CAS-No.) 38668-48-3	0.1 – 1	6.1B: Acute Tox. 2 (Oral), H300 6.4A: Eye Irrit. 2A, H319 9.1D: Aquatic Acute 3, H402 9.1C: Aquatic Chronic 3, H412 9.3A: Ecotoxicity to terrestrial vertebrates A, H431

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

Take off immediately all contaminated clothing. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation

Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact

Wash contaminated clothing before reuse. Wash with plenty of water/... If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact

Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.

First-aid measures after ingestion

Rinse mouth. Get medical advice/attention. Do not induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact

May cause an allergic skin reaction.

Symptoms/effects after eye contact

May cause severe irritation.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

HIT-HY 170, A

Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Water spray. Carbon dioxide. Dry powder. Foam. Sand.
Unsuitable extinguishing media	Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

General measures	Spilled material may present a slipping hazard.
Hazardous decomposition products in case of fire	Thermal decomposition generates : Carbon dioxide. Carbon monoxide.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	Spilled material may present a slipping hazard.
6.1.1. For non-emergency personnel	
Emergency procedures	Evacuate unnecessary personnel.
6.1.2. For emergency responders	
Protective equipment	Use personal protective equipment as required. Equip cleanup crew with proper protection.
Emergency procedures	Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	Collect spillage.
Methods for cleaning up	This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. Store away from other materials.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.
Hygiene measures	Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	Keep cool. Protect from sunlight.
Incompatible products	Strong bases. Strong acids.
Incompatible materials	Sources of ignition. Direct sunlight.
Storage temperature	5 – 25 °C
Heat and ignition sources	Keep away from heat and direct sunlight.

HIT-HY 170, A

Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

Exposure limit values for the other components

Additional information

The product has a pasty consistency. Exposure limit values for respirable dusts are not relevant for this product.

8.2. Monitoring

No additional information available

8.3. Appropriate engineering controls

Appropriate engineering controls

Ensure adequate ventilation.

8.4. Individual protection measures, such as personal protective equipment (PPE)

Hand protection

Wear protective gloves. The permeation time is not the maximum wearing time! Generally speaking, it must be reduced. Contact with either mixtures of substances or different substances may shorten the protective function's effective duration.

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	0,12		EN ISO 374

Eye protection

Wear security glasses which protect from splashes

Type	Field of application	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166, EN 170

Skin and body protection

Wear suitable protective clothing

Personal protective equipment symbol(s)



Environmental exposure controls

Avoid release to the environment.

Consumer exposure controls

Avoid contact during pregnancy/while nursing.

SECTION 9: Physical and chemical properties

Physical state

Solid

Appearance

Thixotropic paste.

Colour

No data available

Odour

No data available

Odour threshold

Not determined

pH

No data available

Evaporation rate

No data available

Relative evaporation rate (butylacetate=1)

No data available

Melting point / Freezing point

No data available

Boiling point

No data available

HIT-HY 170, A

Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

Flash point	> 109 °C DIN EN ISO 1523
Auto-ignition temperature	Not self-igniting
Flammability (solid, gas)	Non flammable.
Vapour pressure	No data available
Relative density	No data available
Density	Density : 1.65 g/ml AW 4.3.23
Solubility	Water : Not miscible
Partition coefficient n-octanol/water (Log Pow)	No data available
Viscosity, kinematic	60606.061 mm²/s
Viscosity, dynamic	100 Pa·s HN-0333
Explosive properties	Product is not explosive.
Explosive limits	No data available
Minimum ignition energy	No data available

SECTION 10: Stability and reactivity

Reactivity	No additional information available
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	No additional information available.
Conditions to avoid	Direct sunlight. Extremely high or low temperatures.
Incompatible materials	Strong acids. Strong bases.
Hazardous decomposition products	fume. Carbon monoxide. Carbon dioxide. Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

1,1'-(p-tolylimino)diprop-2-ol (38668-48-3)	
LD50 oral rat	25 mg/kg
LD50 dermal rat	> 2000 mg/kg
2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
LD50 oral rat	10066 mg/kg
LD50 dermal rat	> 3000 mg/kg
2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
LD50 oral rat	> 5000 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Literature study; >=2000 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	≥ 5000 mg/kg bodyweight (Rabbit; Experimental value)

Skin corrosion/irritation	Not classified
Serious eye damage/irritation	Causes serious eye irritation.
Respiratory or skin sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
STOT-single exposure	Not classified
STOT-repeated exposure	Not classified
Aspiration hazard	Not classified

HIT-HY 170, A

Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

HIT-HY 170, A	
Viscosity, kinematic	60606.061 mm ² /s
Potential adverse human health effects and symptoms	No additional information available.

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	Not classified
Hazardous to the aquatic environment, long-term (chronic)	Not classified
Soil toxicity	Not classified
Terrestrial vertebrate toxicity	Not classified
Terrestrial invertebrate toxicity	Not classified
Other information	Avoid release to the environment.

1,1'-(p-tolylimino)dipropen-2-ol (38668-48-3)	
LC50 - Fish [1]	≈ 17 mg/l
LC50 - Other aquatic organisms [1]	245 mg/l
EC50 - Crustacea [1]	28.8 mg/l
NOEC (acute)	57.8 mg/l
Partition coefficient n-octanol/water (Log Kow)	2.1
	> 2000 mg/kg
LD50 oral rat	25 mg/kg

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
LC50 - Other aquatic organisms [1]	9.79 mg/l
NOEC (acute)	7.51 mg/l
NOEC (chronic)	20 mg/l
Partition coefficient n-octanol/water (Log Pow)	3.1
	> 3000 mg/kg
LD50 oral rat	10066 mg/kg

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
LC50 - Fish [1]	493 mg/l (48 h; Leuciscus idus; GLP)
EC50 - Crustacea [1]	> 143 mg/l (48 h; Daphnia magna; GLP)
ErC50 algae	97.2 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
ErC50 algae	97.2 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
BCF - Fish [1]	≤ 100
BCF - Fish [2]	3.2 Quantitative structure-activity relationship (QSAR)
Partition coefficient n-octanol/water (Log Pow)	0.97 (OECD 102 method)
Partition coefficient n-octanol/water (Log Koc)	1.9 (log Koc, Calculated value)
LD50 dermal rabbit	≥ 5000 mg/kg bodyweight (Rabbit; Experimental value)
LD50 oral rat	> 5000 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Literature study; ≥2000 mg/kg bodyweight; Rat; Experimental value)
Threshold limit - Algae [1]	> 97.2 mg/l (72 h; Pseudokirchneriella subcapitata; GLP)
Threshold limit - Algae [2]	> 97.2 mg/l (72 h; Pseudokirchneriella subcapitata; GLP)

12.2. Persistence and degradability

HIT-HY 170, A	
Persistence and degradability	Not established.

HIT-HY 170, A

Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
Not rapidly degradable	
Biodegradation	84 %
2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
Not rapidly degradable	
Persistence and degradability	Readily biodegradable in water.

12.3. Bioaccumulative potential

HIT-HY 170, A	
Bioaccumulative potential	Not established.
1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)	
Partition coefficient n-octanol/water (Log Kow)	2.1
2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
Partition coefficient n-octanol/water (Log Pow)	3.1
2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
BCF - Fish [1]	≤ 100
BCF - Fish [2]	3.2 Quantitative structure-activity relationship (QSAR)
Partition coefficient n-octanol/water (Log Pow)	0.97 (OECD 102 method)
Partition coefficient n-octanol/water (Log Koc)	1.9 (log Koc, Calculated value)
Bioaccumulative potential	Low bioaccumulation potential (BCF < 500).

12.4. Mobility in soil

HIT-HY 170, A	
Mobility in soil	No additional information available
1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)	
Partition coefficient n-octanol/water (Log Kow)	2.1
2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
Partition coefficient n-octanol/water (Log Pow)	3.1
2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
Partition coefficient n-octanol/water (Log Pow)	0.97 (OECD 102 method)
Partition coefficient n-octanol/water (Log Koc)	1.9 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

Ozone	Not classified
Other adverse effects	No additional information available

SECTION 13: Disposal considerations

Product/Packaging disposal recommendations	After curing, the product can be disposed of with household waste. . Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / RID

ADR	IMDG	IATA	RID
14.1. UN number or ID number			
Not applicable	Not applicable	Not applicable	Not applicable

HIT-HY 170, A

Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

ADR	IMDG	IATA	RID
14.2. UN proper shipping name			
Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)			
Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available			

14.6. Special precautions for user

Overland transport

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

Rail transport

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

14.8. Hazchem or Emergency Action Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health, and environmental national regulations specific for the product

Hazardous Substances and New Organisms Act

HSNO Approval Number

HSR002544

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

SDS Major/Minor

None

Issue date

22/09/2021

Revision date

22/09/2021

Supersedes

23/03/20200

Indication of changes:

Section	Changed item	Change	Comments
2.1	GHS NZ classification	Modified	
2.2	Hazard pictograms (GHS NZ)	Removed	
2.2	Hazard statements (GHS NZ)	Removed	
3	Composition/information on ingredients	Modified	

HIT-HY 170, A

Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

Abbreviations and acronyms

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
 ATE - Acute Toxicity Estimate
 BCF - Bioconcentration factor
 CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
 DMEL - Derived Minimal Effect level
 DNEL - Derived-No Effect Level
 vPvB - Very Persistent and Very Bioaccumulative
 SDS - Safety Data Sheet
 RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
 REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
 PNEC - Predicted No-Effect Concentration
 PBT - Persistent Bioaccumulative Toxic
 OECD - Organisation for Economic Co-operation and Development
 NOEC - No-Observed Effect Concentration
 NOAEL - No-Observed Adverse Effect Level
 NOAEC - No-Observed Adverse Effect Concentration
 LOAEL - Lowest Observed Adverse Effect Level
 LD50 - Median lethal dose
 LC50 - Median lethal concentration
 IMDG - International Maritime Dangerous Goods
 IATA - International Air Transport Association
 EC50 - Median effective concentration
 IARC - International Agency for Research on Cancer
 None.

Other information

Full text of H-statements:

6.1B: Acute Tox. 2 (Oral)	6.1B: Acute toxicity (oral), Category 2
6.4A: Eye Irrit. 2	6.4A: Serious eye damage/eye irritation, Category 2
6.4A: Eye Irrit. 2A	6.4A: Serious eye damage/eye irritation, Category 2A
6.5B: Skin Sens. 1	6.5B: Skin sensitisation, Category 1
9.1C: Aquatic Chronic 3	9.1C: Hazardous to the aquatic environment — Chronic Hazard, Category 3
9.1D: Aquatic Acute 3	9.1D: Hazardous to the aquatic environment — Acute Hazard, Category 3
9.3A: Ecotoxicity to terrestrial vertebrates A	9.3A: Ecotoxicity to terrestrial vertebrates A
Acute Tox. Not classified (Oral)	Acute toxicity (oral) Not classified
Flam. Liq. Not classified	Flammable liquids Not classified
H300	Fatal if swallowed.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H402	Harmful to aquatic life
H412	Harmful to aquatic life with long lasting effects.
H431	Very toxic to terrestrial vertebrates



HIT-HY 170, A

Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

SDS_NZ_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

HIT-HY 170, B

Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

Issue date: 22/09/2021

Revision date: 22/09/2021

Supersedes: 23/03/2020

Version: 1.3

SECTION 1: Identification of the hazardous chemical and of the supplier

1.1 Product identifier

Product name HIT-HY 170, B
Product form Mixture
Product code BU Anchor

1.2 Other means of identification

No additional information available

1.3 Relevant identified uses of the substance or mixture and uses advised against

Recommended use Composite mortar component for fasteners in the construction industry
Restrictions on use For professional use only

1.4 Supplier's details

Supplier
Hilti (New Zealand) Ltd.
Level 1, Building B 600 South Road
Ellerslie
1051 Auckland - New Zealand
T +64 9 571 9995
, 800 444 584 toll free - F +64 9526 7780
servicenz@hilti.com

Department issuing data specification sheet
Hilti Entwicklungsgesellschaft mbH
Hiltistraße 6
86916 Kaufering - Deutschland
T +49 8191 906876
anchor.hse@hilti.com

1.5. Emergency phone number

Emergency number Schweizerisches Toxikologisches Informationszentrum – 24h Service
+41 44 251 51 51 (international)
+64 9 571 9995
; 800 444 584 toll free

Country	Organisation/Company	Address	Emergency number
New Zealand	National Poisons Centre		0800 623 000

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture


HSNO Approval Number HSR002544

6.5B Skin sensitisation, Category 1
9.1A Hazardous to the aquatic environment — Acute Hazard, Category 1
9.1A Hazardous to the aquatic environment — Chronic Hazard, Category 1

2.2. Label elements

GHS NZ labelling

Hazard pictograms (GHS NZ)



Signal word (GHS NZ)

Warning

Contains

dibenzoyl peroxide (5 - 10 %)

Hazard statements (GHS NZ)

H317 - May cause an allergic skin reaction.
H410 - Very toxic to aquatic life with long lasting effects.

Prevention

P280 - Wear eye protection, protective clothing, protective gloves.

HIT-HY 170, B

Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

Response

P262 - Do not get in eyes, on skin, or on clothing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P302+P352 - IF ON SKIN: Wash with plenty of water/...

P337+P313 - If eye irritation persists: Get medical advice/attention.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

2.3. Other hazards not contributing to the classification

No additional information available

SECTION 3: Composition and information of the ingredients of the hazardous chemical

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	Conc.	Classification according to GHS NZ
dibenzoyl peroxide	(CAS-No.) 94-36-0	5 - 10	5.2B: Org. Perox. B, H241 6.4A: Eye Irrit. 2, H319 6.5B: Skin Sens. 1, H317 9.1A: Aquatic Acute 1, H400 (M=10) 9.1A: Aquatic Chronic 1, H410 (M=10)

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

Take off immediately all contaminated clothing. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation

Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact

Wash contaminated clothing before reuse. Wash with plenty of water/... If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact

Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.

First-aid measures after ingestion

Rinse mouth. Get medical advice/attention. Do not induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact

May cause an allergic skin reaction.

Symptoms/effects after eye contact

May cause severe irritation.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray. Carbon dioxide. Dry powder. Foam. Sand.

Unsuitable extinguishing media

Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

General measures

Spilled material may present a slipping hazard.

HIT-HY 170, B

Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

Hazardous decomposition products in case of fire

Thermal decomposition generates : Carbon dioxide. Carbon monoxide.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions

Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.

Protection during firefighting

Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

EAC code

2Z - 2Z

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

Spilled material may present a slipping hazard.

6.1.1. For non-emergency personnel

Emergency procedures

Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment

Use personal protective equipment as required. Equip cleanup crew with proper protection.

Emergency procedures

Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment

Collect spillage.

Methods for cleaning up

This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. Store away from other materials.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.

Hygiene measures

Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

Keep cool. Protect from sunlight.

Incompatible products

Strong bases. Strong acids.

Incompatible materials

Sources of ignition. Direct sunlight.

Storage temperature

5 – 25 °C

Heat and ignition sources

Keep away from heat and direct sunlight.

HIT-HY 170, B

Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

HIT-HY 170, B	
New Zealand - Occupational Exposure Limits	
Local name	Benzoyl peroxide
WES-TWA (OEL TWA) [1]	5 mg/m ³
Remark (NZ)	dse (Dermal sensitiser)
Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 12th Edition
dibenzoyl peroxide (94-36-0)	
New Zealand - Occupational Exposure Limits	
Local name	Benzoyl peroxide
WES-TWA (OEL TWA) [1]	5 mg/m ³
Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 11th Edition

Exposure limit values for the other components

Additional information The product has a pasty consistency. Exposure limit values for respirable dusts are not relevant for this product.

8.2. Monitoring

No additional information available

8.3. Appropriate engineering controls

Appropriate engineering controls Ensure adequate ventilation.

8.4. Individual protection measures, such as personal protective equipment (PPE)

Hand protection Wear protective gloves. The permeation time is not the maximum wearing time! Generally speaking, it must be reduced. Contact with either mixtures of substances or different substances may shorten the protective function's effective duration.

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	0,12		EN ISO 374

Eye protection Wear security glasses which protect from splashes

Type	Field of application	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166, EN 170

Skin and body protection Wear suitable protective clothing

Personal protective equipment symbol(s)



Environmental exposure controls

Avoid release to the environment.

Consumer exposure controls

Avoid contact during pregnancy/while nursing.

HIT-HY 170, B

Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

SECTION 9: Physical and chemical properties

Physical state	Solid
Appearance	Thixotropic paste.
Colour	No data available
Odour	No data available
Odour threshold	Not determined
pH	≈ 6
Evaporation rate	No data available
Relative evaporation rate (butylacetate=1)	No data available
Melting point / Freezing point	No data available
Boiling point	No data available
Flash point	No data available
Auto-ignition temperature	Not self-igniting
Flammability (solid, gas)	Non flammable.
Vapour pressure	No data available
Relative density	No data available
Density	Density : 1.7 g/cm ³ DIN 51757
Solubility	Water : Not miscible
Partition coefficient n-octanol/water (Log Pow)	No data available
Viscosity, kinematic	52941.176 mm ² /s
Viscosity, dynamic	90 Pa·s HN-0333
Explosive properties	Product is not explosive.
Explosive limits	No data available
Minimum ignition energy	No data available
SADT	65 °C

SECTION 10: Stability and reactivity

Reactivity	No additional information available
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	No additional information available.
Conditions to avoid	Direct sunlight. Extremely high or low temperatures.
Incompatible materials	Strong acids. Strong bases.
Hazardous decomposition products	fume. Carbon monoxide. Carbon dioxide. Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified
Skin corrosion/irritation	Not classified
	pH: ≈ 6
Serious eye damage/irritation	Not classified
Respiratory or skin sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified

HIT-HY 170, B

Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

STOT-single exposure	Not classified
STOT-repeated exposure	Not classified
Aspiration hazard	Not classified

HIT-HY 170, B	
Viscosity, kinematic	52941.176 mm ² /s
Potential adverse human health effects and symptoms	No additional information available.

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	Very toxic to aquatic life.
Hazardous to the aquatic environment, long-term (chronic)	Very toxic to aquatic life with long lasting effects.
Soil toxicity	Not classified
Terrestrial vertebrate toxicity	Not classified
Terrestrial invertebrate toxicity	Not classified
Other information	Avoid release to the environment.

dibenzoyl peroxide (94-36-0)	
LC50 - Fish [2]	0.0602 mg/l (96h; Oncorhynchus mykiss; ECHA)
EC50 - Crustacea [1]	0.11 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
ErC50 algae	0.0711 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
ErC50 algae	0.0711 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
NOEC (acute)	0.0316 mg/l (96h; Oncorhynchus mykiss; ECHA)
NOEC chronic fish	0.001 mg/l
Partition coefficient n-octanol/water (Log Pow)	3.71
Partition coefficient n-octanol/water (Log Koc)	3.8 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)

12.2. Persistence and degradability

HIT-HY 170, B	
Persistence and degradability	Not established.
dibenzoyl peroxide (94-36-0)	
Persistence and degradability	Readily biodegradable in water. Not established. May cause long-term adverse effects in the environment.

12.3. Bioaccumulative potential

HIT-HY 170, B	
Bioaccumulative potential	Not established.
dibenzoyl peroxide (94-36-0)	
Partition coefficient n-octanol/water (Log Pow)	3.71
Partition coefficient n-octanol/water (Log Koc)	3.8 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)
Bioaccumulative potential	Low bioaccumulation potential (Log Kow < 4).

12.4. Mobility in soil

HIT-HY 170, B	
Mobility in soil	No additional information available

HIT-HY 170, B

Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

dibenzoyl peroxide (94-36-0)	
Surface tension	No data available (test not performed)
Partition coefficient n-octanol/water (Log Pow)	3.71
Partition coefficient n-octanol/water (Log Koc)	3.8 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)
Ecology - soil	Low potential for mobility in soil.

12.5. Other adverse effects





Ozone	Not classified
Other adverse effects	No additional information available

SECTION 13: Disposal considerations

Product/Packaging disposal recommendations	After curing, the product can be disposed of with household waste. . Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / RID

ADR	IMDG	IATA	RID
14.1. UN number or ID number			
UN 3077	UN 3077	UN 3077	UN 3077
14.2. UN proper shipping name			
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (dibenzoyl peroxide)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (dibenzoyl peroxide)	Environmentally hazardous substance, solid, n.o.s. (dibenzoyl peroxide)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (dibenzoyl peroxide)
Transport document description			
UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (dibenzoyl peroxide), 9, III, (-)	UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (dibenzoyl peroxide), 9, III, MARINE POLLUTANT	UN 3077 Environmentally hazardous substance, solid, n.o.s. (dibenzoyl peroxide), 9, III	UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (dibenzoyl peroxide), 9, III
14.3. Transport hazard class(es)			
9	9	9	9
			
14.4. Packing group			
III	III	III	III
14.5. Environmental hazards			
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
not restricted according ADR Special Provision SP375, IATA-DGR Special Provision A197 and IMDG-Code 2.10.2.7			

14.6. Special precautions for user

Overland transport


Classification code (ADR)	M7
---------------------------	----

HIT-HY 170, B

Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

Special provisions (ADR)	274, 335, 375, 601
Limited quantities (ADR)	5kg
Packing instructions (ADR)	P002, IBC08, LP02, R001
Mixed packing provisions (ADR)	MP10
Transport category (ADR)	3
Orange plates	



Tunnel restriction code (ADR)	-
EAC code	2Z

Transport by sea

Special provisions (IMDG)	274, 335, 966, 967, 969
Limited quantities (IMDG)	5 kg
Packing instructions (IMDG)	LP02, P002
EmS-No. (Fire)	F-A
EmS-No. (Spillage)	S-F
Stowage category (IMDG)	A
Stowage and handling (IMDG)	SW23

Air transport

PCA packing instructions (IATA)	956
PCA max net quantity (IATA)	400kg
CAO packing instructions (IATA)	956
Special provisions (IATA)	A97, A158, A179, A197, A215

Rail transport

Special provisions (RID)	274, 335, 375, 601
Limited quantities (RID)	5kg
Packing instructions (RID)	P002, IBC08, LP02, R001

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

14.8. Hazchem or Emergency Action Code

EAC code	2Z.
----------	-----

SECTION 15: Regulatory information

15.1. Safety, health, and environmental national regulations specific for the product

Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR002544
----------------------	-----------

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

SDS Major/Minor	None
Issue date	22/09/2021
Revision date	22/09/2021
Supersedes	23/03/20200

Indication of changes:

HIT-HY 170, B

Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

Section	Changed item	Change	Comments
14	Transportation information	Modified	

Abbreviations and acronyms

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
 ATE - Acute Toxicity Estimate
 BCF - Bioconcentration factor
 DMEL - Derived Minimal Effect level
 CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
 DNEL - Derived-No Effect Level
 EC50 - Median effective concentration
 IARC - International Agency for Research on Cancer
 IATA - International Air Transport Association
 IMDG - International Maritime Dangerous Goods
 LC50 - Median lethal concentration
 LD50 - Median lethal dose
 LOAEL - Lowest Observed Adverse Effect Level
 NOAEC - No-Observed Adverse Effect Concentration
 NOAEL - No-Observed Adverse Effect Level
 SDS - Safety Data Sheet
 vPvB - Very Persistent and Very Bioaccumulative
 RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
 REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
 PNEC - Predicted No-Effect Concentration
 PBT - Persistent Bioaccumulative Toxic
 None.

Other information

Full text of H-statements:

5.2B: Org. Perox. B	5.2B: Organic Peroxides, Type B
6.4A: Eye Irrit. 2	6.4A: Serious eye damage/eye irritation, Category 2
6.5B: Skin Sens. 1	6.5B: Skin sensitisation, Category 1
9.1A: Aquatic Acute 1	9.1A: Hazardous to the aquatic environment — Acute Hazard, Category 1
9.1A: Aquatic Chronic 1	9.1A: Hazardous to the aquatic environment — Chronic Hazard, Category 1
H241	Heating may cause a fire or explosion.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

SDS_NZ_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

HIT-HY 170

Safety information for 2-Component-products

Issue date: 23/03/2020

Revision date: 23/03/2020

Supersedes: 16/03/2018

Version: 2.0

SECTION 1: Kit identification

1.1 Product identifier

Product name

HIT-HY 170



Product code

BU Anchor

1.2 Details of the supplier of the Safety information for 2-Component-products

Hilti (New Zealand) Ltd.
Level 1, Building B 600 South Road
Ellerslie
1051 Auckland - New Zealand
T +64 9 571 9995
, 800 444 584 toll free - F +64 9526 7780
servicenz@hilti.com

SECTION 2: General information

Storage

Storage temperature : 5 - 25 °C

A SDS for each of these components is included. Please do not separate any component SDS from this cover page

This Kit should be handled in accordance with good laboratory practices and appropriate personal protective equipment should be used

SECTION 3:

Classification of the Product

2.1. Classification of the substance or mixture

EYDA-2
SESK-1
CARC-1B
AEAH-1
AECH-1

6.4A: Eye Irrit. 2
6.5B: Skin Sens. 1
6.7A: Carc. 1B
9.1A: Aquatic Acute 1
9.1A: Aquatic Chronic 1

2.2. Label elements

Hazard pictograms (GHS NZ)



GHS07



GHS08



GHS09

Signal word (GHS NZ)

Danger

Hazard statements (GHS NZ)

H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H350 - May cause cancer.
H410 - Very toxic to aquatic life with long lasting effects.
P280 - Wear eye protection, protective clothing, protective gloves.
P262 - Do not get in eyes, on skin, or on clothing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

Precautionary statements (GHS NZ)

HIT-HY 170

Safety information for 2-Component-products


contact lenses, if present and easy to do. Continue rinsing.
P302+P352 - IF ON SKIN: Wash with plenty of water/...
P337+P313 - If eye irritation persists: Get medical advice/attention.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

2.3. Other hazards not contributing to the classification

No additional information available

Additional information

2-Component-foilpack, contains:
Component A: Urethane methacrylate resin, inorganic filler
Component B: Dibenzoyl peroxide, phlegmatized



Name	General description	Quantity	Unit	Classification according to the United Nations GHS
HIT-HY 170, A		1	pcs	Eye Irrit. 2A, H319 Skin Sens. 1, H317 Carc. 1B, H350
HIT-HY 170, B		1	pcs	Org. Perox. Not classified Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

SECTION 4: General advice

General advice

For professional users only

SECTION 5: Safe handling advice

General measures	Spilled material may present a slipping hazard
Environmental precautions	Prevent entry to sewers and public waters Notify authorities if liquid enters sewers or public waters
Storage conditions	Keep cool. Protect from sunlight.
Precautions for safe handling	Wear personal protective equipment Avoid contact with skin and eyes Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work Provide good ventilation in process area to prevent formation of vapour
Methods for cleaning up	This material and its container must be disposed of in a safe way, and as per local legislation Mechanically recover the product Store away from other materials.
For containment	Collect spillage.
Incompatible materials	Sources of ignition Direct sunlight
Incompatible products	Strong bases Strong acids

SECTION 6: First aid measures

First-aid measures after eye contact	Rinse immediately with plenty of water Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical advice/attention if pain, blinking or redness persists
First-aid measures after ingestion	Rinse mouth Get medical advice/attention.

HIT-HY 170

Safety information for 2-Component-products

First-aid measures after inhalation	Do not induce vomiting Obtain emergency medical attention Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air Allow the victim to rest
First-aid measures after skin contact	Wash contaminated clothing before reuse. Wash with plenty of water/... If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures general	Take off immediately all contaminated clothing. Never give anything by mouth to an unconscious person If you feel unwell, seek medical advice (show the label where possible)
Symptoms/effects after eye contact	May cause severe irritation
Symptoms/effects after skin contact	May cause an allergic skin reaction.

SECTION 7: Fire fighting measures

Firefighting instructions	Use water spray or fog for cooling exposed containers Exercise caution when fighting any chemical fire Prevent fire fighting water from entering the environment
Protection during firefighting	Self-contained breathing apparatus Do not enter fire area without proper protective equipment, including respiratory protection
Hazardous decomposition products in case of fire	Thermal decomposition generates : Carbon dioxide Carbon monoxide

SECTION 8: Other information

No data available

HIT-HY 170, B

Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

Issue date: 23/03/2020

Revision date: 23/03/2020

Supersedes: 16/03/2018

Version: 1.2

SECTION 1: Identification of the hazardous chemical and of the supplier

Product identifier

Product name	HIT-HY 170, B
Product form	Mixture
Product code	BU Anchor

Other means of identification

No additional information available

Relevant identified uses of the substance or mixture and uses advised against

Recommended use	For professional use only Composite mortar component for fasteners in the construction industry
-----------------	--

Supplier's details

Supplier

Hilti (New Zealand) Ltd.
Level 1, Building B 600 South Road
Ellerslie
1051 Auckland - New Zealand
T +64 9 571 9995
, 800 444 584 toll free - F +64 9526 7780
servicenz@hilti.com

Department issuing data specification sheet

Hilti Entwicklungsgesellschaft mbH
Hiltistraße 6
86916 Kaufering - Deutschland
T +49 8191 906876
anchor.hse@hilti.com

Emergency number

Schweizerisches Toxikologisches Informationszentrum – 24h Service
+41 44 251 51 51 (international)
+64 9 571 9995
; 800 444 584 toll free

Country	Organisation/Company	Address	Emergency number
New Zealand	National Poisons Centre		0800 623 000


SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

ORPE-NC	Org. Perox. Not classified
SESK-1	6.5B: Skin Sens. 1
AEAH-1	9.1A: Aquatic Acute 1
AECH-1	9.1A: Aquatic Chronic 1

2.2. Label elements

Hazard pictograms (GHS NZ)



Signal word (GHS NZ)

Warning

Contains

dibenzoyl peroxide

Hazard statements (GHS NZ)

H317 - May cause an allergic skin reaction.
H410 - Very toxic to aquatic life with long lasting effects.

Precautionary statements (GHS NZ)

P280 - Wear eye protection, protective clothing, protective gloves.
P262 - Do not get in eyes, on skin, or on clothing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

HIT-HY 170, B

Safety Data Sheet

P302+P352 - IF ON SKIN: Wash with plenty of water/...
P337+P313 - If eye irritation persists: Get medical advice/attention.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

2.3. Other hazards not contributing to the classification

No additional information available

SECTION 3: Composition and information of the ingredients of the hazardous chemical

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	Conc.	Classification according to the United Nations GHS (Rev. 4, 2011)
dibenzoyl peroxide	(CAS-No.) 94-36-0	5 - 10	5.2B: Org. Perox. B, H241 6.4A: Eye Irrit. 2, H319 6.5B: Skin Sens. 1, H317 9.1A: Aquatic Acute 1, H400 (M=10) 9.1A: Aquatic Chronic 1, H410 (M=10)

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	Take off immediately all contaminated clothing. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	Wash contaminated clothing before reuse. Wash with plenty of water/.... If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	Rinse mouth. Get medical advice/attention. Do not induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	May cause an allergic skin reaction.
Symptoms/effects after eye contact	May cause severe irritation.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Water spray. Carbon dioxide. Dry powder. Foam. Sand.
Unsuitable extinguishing media	Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

General measures	Spilled material may present a slipping hazard.
------------------	---

HIT-HY 170, B

Safety Data Sheet

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	Spilled material may present a slipping hazard.
6.1.1. For non-emergency personnel	
Emergency procedures	Evacuate unnecessary personnel.
6.1.2. For emergency responders	
Protective equipment	Use personal protective equipment as required. Equip cleanup crew with proper protection.
Emergency procedures	Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	Collect spillage.
Methods for cleaning up	This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. Store away from other materials.

SECTION 7: Handling and storage, including how the chemical may be safely used

7.1. Precautions for safe handling

Precautions for safe handling	Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.
Hygiene measures	Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	Keep cool. Protect from sunlight.
Incompatible products	Strong bases. Strong acids.
Incompatible materials	Sources of ignition. Direct sunlight.
Storage temperature	5 - 25 °C
Heat and ignition sources	Keep away from heat and direct sunlight.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

HIT-HY 170, B		
New Zealand	Local name	Benzoyl peroxide
New Zealand	TWA (mg/m ³)	5 mg/m ³

HIT-HY 170, B

Safety Data Sheet

HIT-HY 170, B		
New Zealand	Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 11th Edition
dibenzoyl peroxide (94-36-0)		
New Zealand	Local name	Benzoyl peroxide
New Zealand	TWA (mg/m ³)	5 mg/m ³
New Zealand	Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 11th Edition

Exposure limit values for the other components

No additional information available

8.2. Monitoring

No additional information available

8.3. Appropriate engineering controls

Appropriate engineering controls Ensure good ventilation of the work station.

8.4. Individual protection measures, such as personal protective equipment (PPE)

No additional information available

Hand protection Wear protective gloves. The permeation time is not the maximum wearing time! Generally speaking, it must be reduced. Contact with either mixtures of substances or different substances may shorten the protective function's effective duration.

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	0,12		EN 374

Eye protection Wear security glasses which protect from splashes

Type	Use	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166, EN 170

Skin and body protection Wear suitable protective clothing



Environmental exposure controls

Avoid release to the environment.

Consumer exposure controls

Avoid contact during pregnancy/while nursing.

SECTION 9: Physical and chemical properties

Physical state	Solid
Appearance	Thixotropic paste.
Colour	white
Odour	characteristic
Odour threshold	Not determined
pH	≈ 6
Evaporation rate	No data available
Relative evaporation rate (butylacetate=1)	No data available
Melting point / Freezing point	No data available
Boiling point	No data available
Flash point	No data available
Auto-ignition temperature	Not self-igniting
Flammability (solid, gas)	Non flammable.

HIT-HY 170, B

Safety Data Sheet

Vapour pressure	No data available
Relative density	No data available
Density	Density : 1.7 g/cm ³ DIN 51757
Solubility	Water : Not miscible
Log Pow	No data available
Viscosity	Viscosity, dynamic : 90 Pa·s HN-0333
Explosive properties	Product is not explosive.
Explosive limits	No data available
Minimum ignition energy	No data available
SADT	65 °C

SECTION 10: Stability and reactivity

Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	No additional information available.
Conditions to avoid	Direct sunlight. Extremely high or low temperatures.
Incompatible materials	Strong acids. Strong bases.
Hazardous decomposition products	fume. Carbon monoxide. Carbon dioxide. Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified
Skin corrosion/irritation	Not classified pH: ≈ 6
Serious eye damage/irritation	Not classified
Respiratory or skin sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
STOT-single exposure	Not classified
STOT-repeated exposure	Not classified
Aspiration hazard	Not classified

HIT-HY 170, B	
Viscosity, kinematic (calculated value) (40 °C)	52941.176 mm ² /s
Potential adverse human health effects and symptoms	No additional information available.

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	Very toxic to aquatic life.
Hazardous to the aquatic environment, long-term (chronic)	Very toxic to aquatic life with long lasting effects.
Soil toxicity	Not classified
Terrestrial vertebrate toxicity	Not classified

HIT-HY 170, B

Safety Data Sheet

Terrestrial invertebrate toxicity
Other information

Not classified
Avoid release to the environment.

dibenzoyl peroxide (94-36-0)	
LC50 fish 2	0.0602 mg/l (96h; Oncorhynchus mykiss; ECHA)
EC50 Daphnia 1	0.11 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
ErC50 (algae)	0.0711 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
ErC50 (algae)	0.0711 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
NOEC (acute)	0.0316 mg/l (96h; Oncorhynchus mykiss; ECHA)
NOEC chronic fish	< 0.001
Log Pow	3.71
Log Koc	3.8 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)

12.2. Persistence and degradability

HIT-HY 170, B	
Persistence and degradability	Not established.
dibenzoyl peroxide (94-36-0)	
Persistence and degradability	Readily biodegradable in water. Not established. May cause long-term adverse effects in the environment.

12.3. Bioaccumulative potential

HIT-HY 170, B	
Bioaccumulative potential	Not established.
dibenzoyl peroxide (94-36-0)	
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Bioaccumulative potential	Low bioaccumulation potential (Log Kow < 4).

12.4. Mobility in soil

HIT-HY 170, B	
Mobility in soil	No additional information available
dibenzoyl peroxide (94-36-0)	
Surface tension	No data available (test not performed)
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Ecology - soil	Low potential for mobility in soil.

12.5. Other adverse effects

Ozone	Not classified
Other adverse effects	No additional information available

SECTION 13: Disposal considerations

Product/Packaging disposal recommendations	After curing, the product can be disposed of with household waste. . Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	Avoid release to the environment.

HIT-HY 170, B

Safety Data Sheet

SECTION 14: Transport information

In accordance with ADR / IATA / IMDG / RID

Other information

not restricted according ADR Special Provision SP375, IATA-DGR Special Provision A197 and IMDG-Code 2.10.2.7

ADR Regulatory status: Not regulated

IMDG Regulatory status: Not regulated

IATA Regulatory status: Not regulated

RID Regulatory status: Not regulated

ADR	IMDG	IATA	RID
14.1. UN number			
Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shipping name			
Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)			
Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group			
Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards			
Not regulated	Not regulated	Not regulated	Not regulated
Environmentally hazardous substances derogation applies (quantity of liquids \leq 5 litres or net mass of solids \leq 5 kg)			
not restricted according ADR Special Provision SP375, IATA-DGR Special Provision A197 and IMDG-Code 2.10.2.7			

14.6. Special precautions for user

- Overland transport

Special provisions (ADR) 375

- Transport by sea

No data available

- Air transport

Special provisions (IATA) A197

- Rail transport

Carriage prohibited (RID) No

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health, and environmental national regulations specific for the product

HSNO Approval Number HSR002544

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

SDS Major/Minor None

HIT-HY 170, B

Safety Data Sheet

Issue date 23/03/2020
Revision date 23/03/2020
Supersedes 16/03/20180

Abbreviations and acronyms

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE - Acute Toxicity Estimate
BCF - Bioconcentration factor
DMEL - Derived Minimal Effect level
CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DNEL - Derived-No Effect Level
EC50 - Median effective concentration
IARC - International Agency for Research on Cancer
IATA - International Air Transport Association
IMDG - International Maritime Dangerous Goods
LC50 - Median lethal concentration
LD50 - Median lethal dose
LOAEL - Lowest Observed Adverse Effect Level
NOAEC - No-Observed Adverse Effect Concentration
NOAEL - No-Observed Adverse Effect Level
SDS - Safety Data Sheet
vPvB - Very Persistent and Very Bioaccumulative
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
PNEC - Predicted No-Effect Concentration
PBT - Persistent Bioaccumulative Toxic
None.

Other information

Full text of H-statements:

5.2B: Org. Perox. B	5.2B: Organic Peroxides, Type B
6.4A: Eye Irrit. 2	6.4A: Serious eye damage/eye irritation, Category 2
6.5B: Skin Sens. 1	6.5B: Skin sensitisation, Category 1
9.1A: Aquatic Acute 1	9.1A: Hazardous to the aquatic environment — Acute Hazard, Category 1
9.1A: Aquatic Chronic 1	9.1A: Hazardous to the aquatic environment — Chronic Hazard, Category 1
Org. Perox. Not classified	Organic peroxide Not classified
H241	Heating may cause a fire or explosion.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

SDS_NZ_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

HIT-HY 170, A

Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

Issue date: 23/03/2020

Revision date: 23/03/2020

Supersedes: 16/03/2018

Version: 2.0

SECTION 1: Identification of the hazardous chemical and of the supplier

Product identifier

Product name	HIT-HY 170, A
Product form	Mixture
Product code	BU Anchor

Other means of identification

No additional information available

Relevant identified uses of the substance or mixture and uses advised against

Recommended use	For professional use only Composite mortar component for fasteners in the construction industry
-----------------	--

Supplier's details

Supplier

Hilti (New Zealand) Ltd.
Level 1, Building B 600 South Road
Ellerslie
1051 Auckland - New Zealand
T +64 9 571 9995
, 800 444 584 toll free - F +64 9526 7780
servicenz@hilti.com

Department issuing data specification sheet

Hilti Entwicklungsgesellschaft mbH
Hiltistraße 6
86916 Kaufering - Deutschland
T +49 8191 906876
anchor.hse@hilti.com

Emergency number

Schweizerisches Toxikologisches Informationszentrum – 24h Service
+41 44 251 51 51 (international)
+64 9 571 9995
; 800 444 584 toll free

Country	Organisation/Company	Address	Emergency number
New Zealand	National Poisons Centre		0800 623 000

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EYDA-2A
SESK-1
CARC-1B

6.4A: Eye Irrit. 2A
6.5B: Skin Sens. 1
6.7A: Carc. 1B

2.2. Label elements

Hazard pictograms (GHS NZ)



GHS07

GHS08

Signal word (GHS NZ)

Danger

Contains

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester; 1,2-dihydroxybenzene; 2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol

Hazard statements (GHS NZ)

H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H350 - May cause cancer.

Precautionary statements (GHS NZ)

P280 - Wear eye protection, protective clothing, protective gloves.
P262 - Do not get in eyes, on skin, or on clothing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

HIT-HY 170, A

Safety Data Sheet

contact lenses, if present and easy to do. Continue rinsing.
P302+P352 - IF ON SKIN: Wash with plenty of water/...
P337+P313 - If eye irritation persists: Get medical advice/attention.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

2.3. Other hazards not contributing to the classification

No additional information available

SECTION 3: Composition and information of the ingredients of the hazardous chemical

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	Conc.	Classification according to the United Nations GHS (Rev. 4, 2011)
2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol	(CAS-No.) 27813-02-1	10 - 25	6.4A: Eye Irrit. 2A, H319 6.5B: Skin Sens. 1, H317
2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester	(CAS-No.) 2082-81-7	1 - 2.5	Acute Tox. Not classified (Oral) 6.5B: Skin Sens. 1, H317
1,1'-(p-tolylimino)dipropan-2-ol	(CAS-No.) 38668-48-3	0.1 - 1	9.3A: Ecotoxicity to terrestrial vertebrates A, H431 6.1B: Acute Tox. 2 (Oral), H300 6.4A: Eye Irrit. 2A, H319 9.1D: Aquatic Acute 3, H402 9.1C: Aquatic Chronic 3, H412
1,2-dihydroxybenzene	(CAS-No.) 120-80-9	0.1 - 1	9.3B: Ecotoxicity to terrestrial vertebrates B, H432 6.1C: Acute Tox. 3 (Oral), H301 6.1C: Acute Tox. 3 (Dermal), H311 6.3A: Skin Irrit. 2, H315 6.4A: Eye Irrit. 2A, H319 6.6B: Muta. 2, H341 6.7A: Carc. 1B, H350 9.1D: Aquatic Acute 2, H401

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	Take off immediately all contaminated clothing. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	Wash contaminated clothing before reuse. Wash with plenty of water/.... If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	Rinse mouth. Get medical advice/attention. Do not induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	May cause an allergic skin reaction.
Symptoms/effects after eye contact	May cause severe irritation.

4.3. Indication of any immediate medical attention and special treatment needed

HIT-HY 170, A

Safety Data Sheet

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media
Unsuitable extinguishing media

Water spray. Carbon dioxide. Dry powder. Foam. Sand.
Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

General measures

Spilled material may present a slipping hazard.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions

Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.

Protection during firefighting

Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

Spilled material may present a slipping hazard.

6.1.1. For non-emergency personnel

Emergency procedures

Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment

Use personal protective equipment as required. Equip cleanup crew with proper protection.

Emergency procedures

Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment

Collect spillage.

Methods for cleaning up

This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. Store away from other materials.

SECTION 7: Handling and storage, including how the chemical may be safely used

7.1. Precautions for safe handling

Precautions for safe handling

Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.

Hygiene measures

Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

Keep cool. Protect from sunlight.

Incompatible products

Strong bases. Strong acids.

Incompatible materials

Sources of ignition. Direct sunlight.

Storage temperature

5 - 25 °C

HIT-HY 170, A

Safety Data Sheet

Heat and ignition sources

Keep away from heat and direct sunlight.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

Exposure limit values for the other components

No additional information available

8.2. Monitoring

No additional information available

8.3. Appropriate engineering controls

Appropriate engineering controls

Ensure good ventilation of the work station.

8.4. Individual protection measures, such as personal protective equipment (PPE)

No additional information available

Hand protection

Wear protective gloves. The permeation time is not the maximum wearing time! Generally speaking, it must be reduced. Contact with either mixtures of substances or different substances may shorten the protective function's effective duration.

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	0,12		EN 374

Eye protection

Wear security glasses which protect from splashes

Type	Use	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166, EN 170

Skin and body protection

Wear suitable protective clothing



Environmental exposure controls

Avoid release to the environment.

Consumer exposure controls

Avoid contact during pregnancy/while nursing.

SECTION 9: Physical and chemical properties

Physical state	Solid
Appearance	Thixotropic paste.
Colour	Light grey
Odour	characteristic
Odour threshold	Not determined
pH	No data available
Evaporation rate	No data available
Relative evaporation rate (butylacetate=1)	No data available
Melting point / Freezing point	No data available
Boiling point	No data available
Flash point	> 109 °C DIN EN ISO 1523
Auto-ignition temperature	Not self-igniting
Flammability (solid, gas)	Non flammable.

HIT-HY 170, A

Safety Data Sheet

Vapour pressure	No data available
Relative density	No data available
Density	Density : 1.65 g/ml AW 4.3.23
Solubility	Water : Not miscible
Log Pow	No data available
Viscosity	Viscosity, dynamic : 100 Pa·s HN-0333
Explosive properties	Product is not explosive.
Explosive limits	No data available
Minimum ignition energy	No data available

SECTION 10: Stability and reactivity

Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	No additional information available.
Conditions to avoid	Direct sunlight. Extremely high or low temperatures.
Incompatible materials	Strong acids. Strong bases.
Hazardous decomposition products	fume. Carbon monoxide. Carbon dioxide. Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
LD50 oral rat	> 5000 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Literature study; >=2000 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	>= 5000 mg/kg bodyweight (Rabbit; Experimental value)
2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
LD50 oral rat	10066 mg/kg
LD50 dermal rat	> 3000 mg/kg
1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)	
LD50 oral rat	25 mg/kg
LD50 dermal rat	> 2000 mg/kg
1,2-dihydroxybenzene (120-80-9)	
LD50 oral rat	300 mg/kg
LD50 dermal rat	600 mg/kg
LC50 inhalation rat (Vapours - mg/l/4h)	>= 2.8 mg/l/4h

Skin corrosion/irritation	Not classified
Serious eye damage/irritation	Causes serious eye irritation.
Respiratory or skin sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	May cause cancer.
Reproductive toxicity	Not classified
STOT-single exposure	Not classified
STOT-repeated exposure	Not classified
Aspiration hazard	Not classified

HIT-HY 170, A	
Viscosity, kinematic (calculated value) (40 °C)	60606.061 mm²/s

HIT-HY 170, A

Safety Data Sheet

HIT-HY 170, A

Potential adverse human health effects and symptoms

No additional information available.

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	Not classified
Hazardous to the aquatic environment, long-term (chronic)	Not classified
Soil toxicity	Not classified
Terrestrial vertebrate toxicity	Not classified
Terrestrial invertebrate toxicity	Not classified
Other information	Avoid release to the environment.

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)

LC50 fish 1	493 mg/l (48 h; Leuciscus idus; GLP)
EC50 Daphnia 1	> 143 mg/l (48 h; Daphnia magna; GLP)
ErC50 (algae)	> 97.2 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
ErC50 (algae)	> 97.2 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
BCF fish 1	<= 100
BCF fish 2	3.2 Quantitative structure-activity relationship (QSAR)
Log Pow	0.97 (OECD 102 method)
Log Koc	1.9 (log Koc, Calculated value)
LD50 dermal rabbit	>= 5000 mg/kg bodyweight (Rabbit; Experimental value)
LD50 oral rat	> 5000 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Literature study; >=2000 mg/kg bodyweight; Rat; Experimental value)
Threshold limit algae 1	> 97.2 mg/l (72 h; Pseudokirchneriella subcapitata; GLP)
Threshold limit algae 2	> 97.2 mg/l (72 h; Pseudokirchneriella subcapitata; GLP)

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)

LC50 other aquatic organisms 1	9.79 mg/l
NOEC (acute)	7.51 mg/l
NOEC (chronic)	20 mg/l
Log Pow	3.1
	> 3000 mg/kg
LD50 oral rat	10066 mg/kg

1,1'-(p-tolylimino)dipropen-2-ol (38668-48-3)

LC50 fish 1	≈ 17 mg/l
LC50 other aquatic organisms 1	245 mg/l
EC50 Daphnia 1	28.8 mg/l
NOEC (acute)	57.8 mg/l
BCF fish 1	≈
Log Kow	2.1
	> 2000 mg/kg
LD50 oral rat	25 mg/kg

1,2-dihydroxybenzene (120-80-9)

LC50 fish 1	9.22 mg/l
LC50 other aquatic organisms 1	22 mg/l
	600 mg/kg
LD50 oral rat	300 mg/kg

HIT-HY 170, A

Safety Data Sheet

12.2. Persistence and degradability

HIT-HY 170, A	
Persistence and degradability	Not established.
2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
Not rapidly degradable	
Persistence and degradability	Readily biodegradable in water.
2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
Not rapidly degradable	
Biodegradation	84 %

12.3. Bioaccumulative potential

HIT-HY 170, A	
Bioaccumulative potential	Not established.
2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
BCF fish 1	See section 12.1 on ecotoxicology
BCF fish 2	See section 12.1 on ecotoxicology
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Bioaccumulative potential	Low bioaccumulation potential (BCF < 500).
2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
Log Pow	See section 12.1 on ecotoxicology
1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)	
BCF fish 1	See section 12.1 on ecotoxicology
Log Kow	See section 12.1 on ecotoxicology

12.4. Mobility in soil

HIT-HY 170, A	
Mobility in soil	No additional information available
2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Ecology - soil	Highly mobile in soil.
2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
Log Pow	See section 12.1 on ecotoxicology
1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)	
Log Kow	See section 12.1 on ecotoxicology

12.5. Other adverse effects

Ozone	Not classified
Other adverse effects	No additional information available

SECTION 13: Disposal considerations

Product/Packaging disposal recommendations	After curing, the product can be disposed of with household waste. . Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	Avoid release to the environment.

HIT-HY 170, A

Safety Data Sheet

SECTION 14: Transport information

In accordance with ADR / IATA / IMDG / RID

Other information

No supplementary information available

ADR Regulatory status: Not regulated
IMDG Regulatory status: Not regulated
IATA Regulatory status: Not regulated
RID Regulatory status: Not regulated

ADR	IMDG	IATA	RID
14.1. UN number			
Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shipping name			
Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)			
Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group			
Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards			
Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available			

14.6. Special precautions for user

- Overland transport

- Transport by sea

No data available

- Air transport

No data available

- Rail transport

Carriage prohibited (RID)

No

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health, and environmental national regulations specific for the product

HSNO Approval Number

HSR002544

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

SDS Major/Minor

None

Issue date

23/03/2020

Revision date

23/03/2020

Supersedes

16/03/20180

HIT-HY 170, A

Safety Data Sheet

Indication of changes:

Section	Changed item	Change	Comments
2.1	GHS NZ classification	Modified	
2.2	Hazard statements (GHS NZ)	Modified	
2.2	Hazard pictograms (GHS NZ)	Added	
3	Composition/information on ingredients	Modified	
16	Indication of changes	Added	

Abbreviations and acronyms

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
 ATE - Acute Toxicity Estimate
 BCF - Bioconcentration factor
 CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
 DMEL - Derived Minimal Effect level
 DNEL - Derived-No Effect Level
 vPvB - Very Persistent and Very Bioaccumulative
 SDS - Safety Data Sheet
 RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
 REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
 PNEC - Predicted No-Effect Concentration
 PBT - Persistent Bioaccumulative Toxic
 OECD - Organisation for Economic Co-operation and Development
 NOEC - No-Observed Effect Concentration
 NOAEL - No-Observed Adverse Effect Level
 NOAEC - No-Observed Adverse Effect Concentration
 LOAEL - Lowest Observed Adverse Effect Level
 LD50 - Median lethal dose
 LC50 - Median lethal concentration
 IMDG - International Maritime Dangerous Goods
 IATA - International Air Transport Association
 EC50 - Median effective concentration
 IARC - International Agency for Research on Cancer
 None.

Other information

Full text of H-statements:

6.1B: Acute Tox. 2 (Oral)	6.1B: Acute toxicity (oral), Category 2
6.1C: Acute Tox. 3 (Dermal)	6.1C: Acute toxicity (dermal), Category 3
6.1C: Acute Tox. 3 (Oral)	6.1C: Acute toxicity (oral), Category 3
6.3A: Skin Irrit. 2	6.3A: Skin corrosion/irritation, Category 2
6.4A: Eye Irrit. 2A	6.4A: Serious eye damage/eye irritation, Category 2A
6.5B: Skin Sens. 1	6.5B: Skin sensitisation, Category 1
6.6B: Muta. 2	6.6B: Germ cell mutagenicity, Category 2
6.7A: Carc. 1B	6.7A: Carcinogenicity, Category 1B
9.1C: Aquatic Chronic 3	9.1C: Hazardous to the aquatic environment — Chronic Hazard, Category 3
9.1D: Aquatic Acute 2	9.1D: Hazardous to the aquatic environment — Acute Hazard, Category 2

HIT-HY 170, A

Safety Data Sheet

9.1D: Aquatic Acute 3	9.1D: Hazardous to the aquatic environment — Acute Hazard, Category 3
9.3A: Ecotoxicity to terrestrial vertebrates A	9.3A: Ecotoxicity to terrestrial vertebrates A
9.3B: Ecotoxicity to terrestrial vertebrates B	9.3B: Ecotoxicity to terrestrial vertebrates B
Acute Tox. Not classified (Oral)	Acute toxicity (oral) Not classified
H300	Fatal if swallowed.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H412	Harmful to aquatic life with long lasting effects.
H431	Very toxic to terrestrial vertebrates
H432	Toxic to terrestrial vertebrates

SDS_NZ_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.